Section 1 Identification Page E1 of E2

INNOVATING SCIENCE®

"Cutting edge science for the classroom"

221 Rochester Street Avon, NY 14414-9409 (585) 226-6177 CHEMTREC 24 Hour Emergency Phone Number (800) 424-9300

For laboratory and industrial use only. Not for drug, food or household use.

Product	CARBOL FUCHSIN SOLUTION (ZIEHL-NEELSEN)

Synonyms None

Section 2 Hazards identification

Signal word: DANGER

Pictograms: GHS02 / GHS05 / GHS07 / GHS08

Target organs: Eyes, Central nervous system, Liver, Kidneys.











Flammable liquid (Category 3)
Skin irritation (Category 2)
Eye damage (Category 1)
Acute toxicity, inhalation (Category 4)
Mutagenicity (Category 2)
Carcinogenicity (Category 2)
STOT-SE (Category 3)
STOT-SE (Category 2)

GHS Label information: Hazard statement:

H226: Flammable liquid and vapour.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H332: Harmful if inhaled.

H336: May cause drowsiness or dizziness. H341: Suspected of causing genetic defects.

H351: Suspected of causing genetic of H351: Suspected of causing cancer. H371: May cause damage to organs.

Hazards not otherwise classified:

Health hazards not otherwise classified (HHNOC) - Vesicant Physical hazards not otherwise classified (PHNOC) - Not Known

Precautionary statement:

P201: Obtain special instructions before use

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233: Keep container tightly closed.

P241: Use explosion-proof electrical/ventilating/lighting equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P260: Do not breathe mist/vapours/spray.

P264: Wash hands thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for 15 minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P310: Immediately call a POISON CENTER or doctor.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P332+P313: If skin irritation occurs: Get medical attention.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P313: IF exposed or concerned: Get medical attention.

P370+P378: In case of fire: Use dry chemical, alcohol foam, carbon dioxide or water spray to extinguish.

P403+P233+P235: Store in a well-ventilated place. Keep container tightly closed.

Keep cool.

P405: Store locked up.

P501: Dispose of contents/container to a licensed chemical disposal agency in

accordance with local/regional/national regulations.

Section 3 Composition / information on ingredients						
Chemical Name	CAS#	%	EINECS			
Water	7732-18-5	85.81%	231-791-2			
Ethyl alcohol, denatured*	64-17-5	9.51%	200-578-6			
Phenol	108-95-2	4.39%	203-632-7			
Basic fuchsin (Magenta)	569-61-9	0.29%	209-321-2			
*Denaturants:						
Isopropyl alcohol	67-63-0	0.813%	200-661-7			
Water	7732-18-5	0.47%	231-791-2			
Methanol	67-56-1	0.36-0.46%	200-659-6			
Methyl isobutyl ketone	108-10-1	0.08-0.09%	203-550-1			

Section 4 First aid measures

INGESTION: MAY BE HARMFUL IF SWALLOWED. Call physician or Poison Control Center immediately. Induce vomiting only if advised by appropriate medical personnel. Never give anything by mouth to an unconscious person.

INHALATION: MAY BE HARMFUL IF INHALED. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

EYE CONTACT: CAUSES SERIOUS EYE IRRITATION/DAMAGE. Check for and remove contact lenses. Flush thoroughly with water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get immediate medical attention.

SKIN ABSORPTION: MAY BE HARMFUL IF ABSORBED THROUGH SKIN. CAUSES SKIN IRRITATION. Remove contaminated clothing. Flush thoroughly with mild soap and water. If irritation occurs, get medical attention.

Section 5 Fire fighting measures

Suitable Extinguishing Media: Carbon dioxide, dry chemical, dry sand, alcohol foam.

Protective Actions for Fire-fighters: In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus and full protective gear. Use water spray to keep fire-exposed containers cool.

Specific Hazards: During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Vapors formed from this product are heavier than air and may travel along the ground to a distant source of ignition and flash back instantly. Flame may not be visible in daylight.

Section 6 Accidental release measures

Personal Precautions: Evacuate personnel to safe area. Use proper personal protective equipment as indicated in Section 8. Provide adequate ventilation.

Environmental Precautions: Avoid runoff into storm sewers and ditches which lead to waterways.

Containment and Cleanup: Remove all sources of ignition. Absorb with inert dry material, sweep or vacuum up and place in a suitable container for proper disposal. Wash spill area with soap and water.

Precautions for Safe Handling: Read label on container before using. Do not wear contact lenses when working with chemicals. Keep out of reach of children. Avoid contact with eyes, skin and clothing. Do not inhale vapors, spray or mist. Use with adequate ventilation. Avoid ingestion. Wash thoroughly after handling. Remove and

Conditions for Safe Storage: Store in a cool, dry, well-ventilated area away from incompatible substances. Keep away from ignition sources.

Section 8	Exposure controls / personal protection							
Exposure Limits:	Chemical Name	ACGIH (TLV)	OSHA (PEL)	NIOSH (REL)				
Exposure Limits:	Ethanol	STEL: 1000 ppm / 1880 mg/m ³ (A3)	TWA: 1000 ppm / 1900 mg/m ³	TWA: 1000 ppm / 1900 mg/m ³				

Engineering controls: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower and fire extinguishing material. Personnel should wear safety glasses, goggles, or faceshield, lab coat or apron, appropriate protective gloves. Use adequate ventilation to keep airborne concentrations low.

Respiratory protection: None should be needed in normal laboratory handling at room temperatures. If misty conditions prevail, work in fume hood or wear a NIOSH/MSHAapproved respirator.

Section 9 Physical and chemical properties

Appearance: Clear red liquid Odor: Mild characteristic odor. Odor threshold: Data not available.

Melting / Freezing point: 0°C (32°F) [water] Boiling point: 100°C (212°F) [water] Flash point: 49°C (120°F) [10% ethanol]

Evaporation rate (Water = 1): >1 Flammability (solid/gas): Data not available.

Explosion limits: Lower / Upper: 4.0%(V) / 20.0%(V)*

Vapor pressure (mm Hg): 14 [water] Vapor density (Air = 1): 0.7 [water]

Relative density (Specific gravity): Approximately 1.0 Solubility(ies): Completely soluble in water.

Partition coefficient: Data not available Auto-ignition temperature: Data not available Decomposition temperature: Data not available

Viscosity: Data not available Molecular formula: Mixture Molecular weight: Mixture

*[Ethanol]

Section 10 Stability and reactivity

Chemical stability: Stable Hazardous polymerization: Will not occur. Conditions to avoid: Excessive temperatures, heat, sparks, open flame and other sources of ignition.

Incompatible materials: Strong oxidizing agents, acids, halogens and calcium hypochlorite. Hot phenol attacks aluminum, lead, magnesium and zinc and the phenol is discolored. The discoloration of phenol is catalyzed by iron and copper.

Hazardous decomposition products: Oxides of carbon.

Section 11 **Toxicological information**

Acute toxicity: Oral-rat LD50: 7060 mg/kg; Inhalation-rat LC50: 124.7 mg/l/4hours [Ethanol]

Skin corrosion/irritation: Skin-rabbit - Slight irritant. Serious eye damage/irritation: Eyes-rabbit - Severe irritant. Respiratory or skin sensitization: Data not available

Germ cell mutagenicity: Data not available

Carcinogenity: Data not available

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

IARC classified: Group 2B: Possibly carcinogenic to humans. [Magenta]

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

CA Prop 65: 🛦 WARNING! : This product can expose you to chemicals including Methanol and Methyl isobutyl ketone, which are known to the State of California to cause cancer and birth defects or other reproductive harm.

Reproductive toxicity: Data not available

STOT-single exposure: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT-repeated exposure: Data not available Aspiration hazard: Data not available

Potential health effects:

Inhalation: Inhalation may cause dizziness, drowsiness, nausea, vomiting, inability to concentrate and irritation of the throat. Ingestion: Ingestion causes dizziness, drowsiness, decreased reaction, euphoria, nausea, vomiting, staggering gait and coma.

Skin: Contact with skin causes irritation defatting on prolonged contact.

Eyes: Contact with eyes may cause corneal damage.

Signs and symptoms of exposure: See Potential health effects above.

Additional information: RTECS #: KQ6300000 [Ethanol]

Ecological information

Toxicity to fish: Oncorhynchus mykiss (fish, fresh water), LC50 = 11,200 mg/l/24 hours [Ethanol]

Toxicity to daphnia and other aquatic invertebrates: Daphnia magna (Crustacia), EC50 = 10,800 mg/l/24 hours [Ethanol, 99.8% pure]

Toxicity to algae: Chlorella pyrenoidosa (Algae), EC50 = 9,310 mg/l/growth rate [Ethanol, absolute] Persistence and degradability: No data available Bioaccumulative potential: No data available Mobility in soil: No data available PBT and vPvB assessment: No data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Disposal considerations

These disposal guidelines are intended for the disposal of catalog-size quantities only. Federal regulations may apply to empty container. State and/or local regulations may be different. Dispose of in accordance with all local, state and federal regulations or contract with a licensed chemical disposal agency.

Section 14 Transport information

UN/NA number: UN1992 Shipping name: Flammable liquids, toxic, n.o.s., (Ethyl alcohol, Phenol solution)

Hazard class: 3, (6.1) Packing group: III Reportable Quantity: No Marine pollutant: No

2020 ERG Guide # 131 **Exceptions:** Limited quantity equal to or less than 5 L

Section 15 Regulatory information

A chemical is considered to be listed if the CAS number for the anhydrous form is on the Inventory list

A continuous to considered to be noted in the content and aninyarous form to on the inventory not.						
Component	TSCA	CERLCA (RQ)	RCRA code	DSL	NDSL	CA Prop 65
Ethanol Phenol	Listed Listed	Not listed Not listed	D001 U188	Listed Listed	Not listed Not listed	▲ WARNING -Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

Section 16 Other information

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. NTP: National Toxicology Program, IARC: International Agency for Research on Cancer, OSHA: Occupational Safety and Health Administration, STOT: Specific Target Organ Toxicity, SE: Single Exposure, RE: Repeated Exposure, ERG: Emergency Response Guidebook

Revision Date: November 3, 2022 Supercedes: August 19, 2022 Form 06/2015

Identification Section 1 Page E1 of E2

INNOVATING SCIENCE

"Cutting edge science for the classroom"

221 Rochester Street Avon, NY 14414-9409 (585) 226-6177

CHEMTREC 24 Hour Emergency Phone Number (800) 424-9300

For laboratory and industrial use only. Not for drug, food or household use.

CARBOL ROSE BENGAL SOLUTION Product

Synonyms

Section 2 Hazards identification

Signal word: DANGER

Pictograms: GHS02 / GHS05 / GHS06 / GHS08

Target organs: Kidneys, Liver, Central nervous system, Eyes











Flammable liquid (Category 3) Acute toxicity, oral (Category 4) Acute toxicity, dermal (Category 4) Skin corrosivity (Category 1B) Acute toxicity, inhalation (Category 3) Mutagenicity (Category 2) STOT-SE (Category 2)

GHS Label information: Hazard statement:

H226: Flammable liquid and vapour.

H302: Harmful if swallowed

H312: Harmful in contact with skin.

H314: Causes severe skin burns and eye damage.

H331: Toxic if inhaled.

H341: Suspected of causing genetic defects.

H373: May cause damage to organs through prolonged or repeated exposure.

Precautionary statement:

P201: Obtain special instructions before use

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233: Keep container tightly closed.

P241: Use explosion-proof electrical/ventilating/lighting equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P260: Do not breathe mist/vapours/spray.

P264: Wash hands thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P310: Immediately call a POISON CENTER or doctor.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for 15 minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P314: Get medical attention if you feel unwell.

P362+P364: Take off contaminated clothing and wash it before reuse.

P370+P378: In case of fire: Use dry chemical, CO₂, water spray or regular foam to extinguish.

P403+P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

P501: Dispose of contents/container to a licensed chemical disposal agency in

accordance with local/regional/national regulations.

Hazards not otherwise classified:

Health hazards not otherwise classified (HHNOC) - Vesicant, rapidly absorbed through skin

Physical hazards not otherwise classified (PHNOC) - Not Know

Section 3 Composition / inf	ormation on ingredients			
Chemical Name	CAS#	%	EINECS	
Water	7732-18-5	86.42%	231-791-2	
Ethyl alcohol	64-17-5	7.31 - 7.38%	200-578-6	
Phenol	108-95-2	4.43 - 4.53%	203-632-7	
Isopropyl alcohol	67-63-0	0.77%	200-661-7	
Rose bengal	632-69-9	0.45%	211-183-3	
Methanol	67-56-1	0.34 - 0.37%	200-659-6	
Methyl isobutyl ketone	108-10-1	0.08 - 0.09%	203-550-1	

Section 4 First aid measures

INGESTION: TOXIC IF SWALLOWED. Call physician or Poison Control Center immediately. Induce vomiting only if advised by appropriate medical personnel. Never give anything by mouth to an unconscious person.

INHALATION: TOXIC IF INHALED. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

EYE CONTACT: CAUSES SEVERE EYE DAMAGE. Check for and remove contact lenses. Flush thoroughly with water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get immediate medical attention.

SKIN ABSORPTION: TOXIC IN CONTACT WITH SKIN. CAUSES SEVERE SKIN BURNS. Remove contaminated clothing. Flush thoroughly with mild soap and water. If irritation occurs, get medical attention

Section 5 Fire fighting measures

Suitable Extinguishing Media: In case of fire: Use dry chemical, CO2, water spray or regular foam to extinguish.

Protective Actions for Fire-fighters: In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus and full protective gear. Use water spray to keep

Specific Hazards: During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Yields flammable and toxic vapors when heated. Water containing phenol may cause severe chemical burns. Above 79°C explosive vapor/air mixtures may be formed.

Accidental release measures

Personal Precautions: Evacuate personnel to safe area. Use proper personal protective equipment as indicated in Section 8. Provide adequate ventilation.

Environmental Precautions: Avoid runoff into storm sewers and ditches which lead to waterways

Containment and Cleanup: Remove all sources of ignition. Absorb with inert dry material, sweep or vacuum up and place in a suitable container for proper disposal. Wash spill area with soap and water.

Precautions for Safe Handling: Read label on container before using. Do not wear contact lenses when working with chemicals. Keep out of reach of children. Avoid contact with eyes, skin and clothing. Do not inhale vapors, spray or mist. Use with adequate ventilation. Avoid ingestion. Wash thoroughly after handling. Remove and wash clothing before reuse.

Conditions for Safe Storage: Store in a cool, well-ventilated area away from incompatible substances. Keep away from ignition sources.

Section 8	Exposure controls / personal protection						
Exposure Limits:	Chemical Name	ACGIH (TLV)	OSHA (PEL)	NIOSH (REL)			
Exposure Limits:	Phenol	TWA: 5 ppm / 19 mg/m ³ (A4)	TWA: 5 ppm / 19 mg/m ³	TWA: 5 ppm / 19 mg/m ³			

Engineering controls: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower and fire extinguishing material. Personnel should wear safety glasses, goggles, or faceshield, lab coat or apron, appropriate protective gloves. Use adequate ventilation to keep airborne concentrations low.

Respiratory protection: Use only in well ventilated area. Work in fume hood and wear a NIOSH/MSHA-approved respirator.

Physical and chemical properties Section 9

Appearance: Liquid. Red color.

Odor: Penol odor

Odor threshold: Data not available

pH: Data not available

Melting / Freezing point: Approximately 0°C (32°F) (water) **Boiling point:** Approximately 100°C (212°F) (water)

Flash point: 49°C (120°F) 10% Ethanol

Evaporation rate (Water = 1): >1

Flammability (solid/gas): Data not available. Explosion limits: Lower: 4% (V) Upper: 20% (V)

Vapor pressure (mm Hg): 14 (water) Vapor density (Air = 1): 0.7 (water)

Relative density (Specific gravity): Approximately 1.0 (water)

Solubility(ies): Complete in water

Partition coefficient: Data not available Auto-ignition temperature: Data not available Decomposition temperature: Data not available.

Viscosity: Data not available. Molecular formula: Mixture Molecular weight: Mixture

Section 10 Stability and reactivity

Chemical stability: Stable Hazardous polymerization: Will not occur. Conditions to avoid: Avoid overheating. Vapors flammable and toxic. Discolors upon prolonged heating.

Incompatible materials: Avoid contact with strong oxidizers, halogens and calcium hypochlorite. Hot phenol attacks aluminum, lead, magnesium and zinc and the phenol is discolored. The discolorization of phenol is catalyzed by iron and copper.

Hazardous decomposition products: Carbon oxides and phenol fumes.

Section 11 **Toxicological information**

Acute toxicity: Phenol: Oral-rat LD50: 317 mg/kg; Dermal-rat LD50: 669 mg/kg Ethanol: Inhalation-rat LC50: 124.7 mg/l/4 hours

Skin corrosion/irritation: Data not available Serious eye damage/irritation: Data not available Respiratory or skin sensitization: Data not available

Germ cell mutagenicity: Data not available

Carcinogenity: Data not available

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

IARC classified: Group 3: Not classifiable as to its carcinogenicity to humans. [Phenol]

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

CA Prop 65: 🛦 WARNING! : This product can expose you to chemicals including Methanol and Methyl isobutyl ketone, which are known to the State of California to cause cancer and birth defects or other reproductive harm.

Reproductive toxicity: Data not available STOT-single exposure: Data not available STOT-repeated exposure: Data not available Aspiration hazard: Data not available Potential health effects: AVOID ALL CONTACT!

Inhalation: Inhalation causes sore throat, burning sensation, cough, dizziness, headache, nausea, vomiting, shortness of breath, labored breathing, unconciousness. Symptoms

may be delayed.

Ingestion: Ingestion causes abdominal pain, convulsions, diarrhea. shock or collapse, sore throat.

Skin: EASILY ABSORBED! Contact causes serious skin burns, numbness, convulsions, collapse, unconsciousness.

Eves: Contact causes pain, redness, loss of vision, severe deep burns.

Signs and symptoms of exposure: Phenol has been found to cause cancer in laboratory animals. May cause adverse mutagenic or teratogenic effects. Exercise appropriate

procedures to minimize potential hazards.

Additional information: RTECS #: Phenol: SJ3325000 Ethanol: KQ6300000

Section 12 **Ecological information**

Toxicity to fish: Oncorhynchus mykiss (fish, fresh water), LC50 = 11,200 mg/l/24 hours [Ethanol]

Toxicity to daphnia and other aquatic invertebrates: Daphnia magna (Crustacea), EC50 = 10,800 mg/l/24 hours [Ethanol, 99.8% pure]

Toxicity to algae: Chlorella pyrenoidosa (Algae), EC50 = 9,310 mg/l/growth rate [Ethanol, absolute] Persistence and degradability: No data available Bioaccumulative potential: No data available Mobility in soil: No data available PBT and vPvB assessment: No data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Disposal considerations

These disposal guidelines are intended for the disposal of catalog-size quantities only. Federal regulations may apply to empty container. State and/or local regulations may be different. Dispose of in accordance with all local, state and federal regulations or contract with a licensed chemical disposal agency.

Section 14 Transport information

UN/NA number: UN1992 Shipping name: Flammable liquids, toxic, n.o.s., (Ethyl alcohol, Phenol solution)

Hazard class: 3, (6.1) Packing group: III Reportable Quantity: No Marine pollutant: No

2020 SERG Guide # 131 **Exceptions:** Limited quantity equal to or less than 5 Lt

Section 15 Regulatory information

A chemical is considered to be listed if the CAS number for the anhydrous form is on the Inventory list.

Component	TSCA	CERLCA (RQ)	RCRA code	DSL	NDSL	CA Prop 65
Phenol Ethanol	Listed Listed	1,000 lbs (454 kg) Not listed	Not listed D001	Listed Listed	Not listed Not listed	★ WARNING -Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

Section 16 Other information

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. NTP: National Toxicology Program, IARC: International Agency for Research on Cancer, OSHA: Occupational Safety and Health Administration, STOT: Specific Target Organ Toxicity, SE: Single Exposure, RE: Repeated Exposure, ERG: Emergency Response Guidebook

Revision Date: August 19, 2022 Supercedes: September 22, 2020 Form 06/2015

Identification Section 1 Page E1 of E2

INNOVATING SCIENCE

"Cutting edge science for the classroom"

(585) 226-6177

CHEMTREC 24 Hour Emergency Phone Number (800) 424-9300

For laboratory and industrial use only. Not for drug, food or household use.

CRYSTAL VIOLET, 1% ALCOHOL SOLUTION Product

Synonyms

Section 2 Hazards identification

Signal word: DANGER

Pictograms: GHS02 / GHS08 / GHS06

Target organs: Eyes, Central nervous system, Liver, Kidneys.







GHS Classification:

Flammable liquid (Category 2) Acute toxicity, oral (Category 3) Acute toxicity, dermal (Category 3) Acute toxicity, inhalation (Category 3) Eye irritation (Category 2B) STOT-SE (Category 2) STOT-SE (Category 3)

GHS Label information: Hazard statement:

H225: Highly flammable liquid and vapour.

H301: Toxic if swallowed

H311: Toxic in contact with skin.

H319: Causes serious eye irritation.

H331: Toxic if inhaled

H336: May cause drowsiness or dizziness.

H371: May cause damage to organs.

Precautionary statement:

P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking

P233+P235: Keep container tightly closed. Keep cool. P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge

P260: Do not breathe mist/vapours/spray. P264: Wash hands thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor. P305+P351+P338: IF IN EYES: Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for

breathing. P308+P311: IF exposed or concerned: Call a POISON CENTER or doctor.

P337+P313: If eye irritation persists: Get medical attention.

P361+P364: Take off immediately all contaminated clothing and wash it before reuse.

P370+P378: In case of fire: Use dry chemical, alcohol foam, carbon dioxide or water spray to extinguish.

P403+P405: Store in a well-ventilated place. Store locked up.

P501: Dispose of contents/container to a licensed chemical disposal agency in accordance with local/regional/national regulations.

Hazards not otherwise classified:

Health hazards not otherwise classified (HHNOC) - Not Known Physical hazards not otherwise classified (PHNOC) - Not Known

Section 3 Composition / information	on ingredients			
Chemical Name	CAS#	%	EINECS	
Ethyl alcohol	64-17-5	84.15 - 84.94%	200-578-6	
Isopropyl alcohol	67-63-0	8.91%	200-661-7	
Methanol	67-56-1	3.96 - 4.26%	200-659-6	
Crystal violet, biological stain and/or pH indicator	548-62-9	1.0%	208-953-6	
Methyl isobutyl ketone	108-10-1	0.89 - 0.99%	203-550-1	

Section 4 First aid measures

INGESTION: TOXIC IF SWALLOWED. Call physician or Poison Control Center immediately. Induce vomiting only if advised by appropriate medical personnel. Never give anything by mouth to an unconscious person.

INHALATION: TOXIC IF INHALED. CAUSES RESPIRATORY TRACT IRRITATION. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

EYE CONTACT: CAUSES SERIOUS EYE IRRITATION. Check for and remove contact lenses. Flush thoroughly with water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get immediate medical attention.

SKIN ABSORPTION: TOXIC IN CONTACT WITH SKIN. CAUSES SKIN IRRITATION. Remove contaminated clothing. Flush thoroughly with mild soap and water. If irritation occurs, get medical attention.

Section 5 Fire fighting measures

Suitable Extinguishing Media: Carbon dioxide, dry chemical, dry sand, alcohol foam.

Protective Actions for Fire-fighters: In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus and full protective gear. Use water spray to keep

Specific Hazards: During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Vapors formed from this product are heavier than air and may travel along the ground to a distant source of ignition and flash back instantly. Flame may not be visible in daylight.

Accidental release measures

Personal Precautions: Evacuate personnel to safe area. Use proper personal protective equipment as indicated in Section 8. Provide adequate ventilation.

Environmental Precautions: Avoid runoff into storm sewers and ditches which lead to waterways

Containment and Cleanup: Remove all sources of ignition. Absorb with inert dry material, sweep or vacuum up and place in a suitable container for proper disposal. Wash spill area with soap and water.

Precautions for Safe Handling: Read label on container before using. Do not wear contact lenses when working with chemicals. Keep out of reach of children. Avoid contact with eyes, skin and clothing. Do not inhale vapors, spray or mist. Use with adequate ventilation. Avoid ingestion. Wash thoroughly after handling. Remove and wash clothing before reuse.

Conditions for Safe Storage: Store in a cool, dry, well-ventilated area away from incompatible substances. Keep away from ignition sources.

Section 8	Exposure controls / personal protection						
Exposure Limits:	Chemical Name	ACGIH (TLV)	OSHA (PEL)	NIOSH (REL)			
Exposure Limits:	Ethanol	STEL: 1000 ppm / 1880 mg/m ³ (A3)	TWA: 1000 ppm / 1900 mg/m ³	TWA: 1000 ppm / 1900 mg/m ³			

Engineering controls: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower and fire extinguishing material. Personnel should wear safety glasses, goggles, or faceshield, lab coat or apron, appropriate protective gloves. Use adequate ventilation to keep airborne concentrations low.

Respiratory protection: None should be needed in normal laboratory handling at room temperatures. If misty conditions prevail, work in fume hood or wear a NIOSH/MSHAapproved respirator.

Section 9 Physical and chemical properties

Appearance: Clear, colorless liquid. Odor: Mild characteristic odor. Odor threshold: Data not available

pH: Data not available

Melting / Freezing point: -114°C (-173°F) Boiling point: 74-80°C (165.2-176°F)

Flash point: 13°C (55°F) CC

Evaporation rate (Butyl acetate = 1): Ca 2 Flammability (solid/gas): Data not available Explosion limits: Lower / Upper: 3.3% / 19.0% Vapor pressure (mm Hg): Ca 50 @ 20°C

Vapor density (Air = 1): Ca 1.5

Relative density (Specific gravity): 0.7919-0.7955°C @ 60/60°F

Solubility(ies): Soluble in water.

Partition coefficient: (n-octanol / water): Low Pow: -.32

Auto-ignition temperature: 363°C (685°F) Decomposition temperature: Data not available Viscosity: Data not available.

Molecular formula: Mixture Molecular weight: Mixture

[Ethanol]

Section 10 Stability and reactivity

Chemical stability: Stable Hazardous polymerization: Will not occur. Conditions to avoid: Excessive temperatures, heat, sparks, open flame and other sources of ignition.

Incompatible materials: Strong oxidizers, inorganic acids and halogens.

Hazardous decomposition products: Carbon oxides.

Section 11 **Toxicological information**

Acute toxicity: Oral-rat LD50: 7060 mg/kg; Inhalation-rat LC50: 124.7 mg/l/4hours

Skin corrosion/irritation: Skin-rabbit - Slight irritant. Serious eye damage/irritation: Eyes-rabbit - Severe irritant. Respiratory or skin sensitization: Data not available

Germ cell mutagenicity: Data not available

Carcinogenity: Data not available

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

IARC classified: Group 3: Not classifiable as to its carcinogenicity to humans. [Isopropanol]

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

CA Prop 65: 🕰 WARNING! : This product can expose you to chemicals including Crystal Violet, Methanol, and Methyl isobutyl ketone, which are known to the State of California to cause cancer and birth defects or other reproductive harm.

Reproductive toxicity: Data not available

STOT-single exposure: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT-repeated exposure: Data not available Aspiration hazard: Data not available

Potential health effects:

Inhalation: Inhalation may cause dizziness, drowsiness, nausea, vomiting, inability to concentrate and irritation of the throat. Ingestion: Ingestion causes dizziness, drowsiness, decreased reaction, euphoria, nausea, vomiting, staggering gait and coma,

Skin: Contact with skin causes irritation defatting on prolonged contact.

Eyes: Contact with eyes may cause blindness.

Signs and symptoms of exposure: See Potential health effects above.

Additional information: RTECS #: KQ6300000 [Ethyl alcohol], B09000000 [Crystal violet]

Ecological information

Toxicity to fish: Oncorhynchus mykiss (fish, fresh water), LC50 = 11,200 mg/l/24 hours [Ethanol]

Toxicity to daphnia and other aquatic invertebrates: Daphnia magna (Crustacia), EC50 = 10,800 mg/l/24 hours [Ethanol, 99.8% pure]

Toxicity to algae: Chlorella pyrenoidosa (Algae), EC50 = 9,310 mg/l/growth rate [Ethanol, absolute] Persistence and degradability: No data available Bioaccumulative potential: No data available Mobility in soil: No data available PBT and vPvB assessment: No data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Disposal considerations

These disposal guidelines are intended for the disposal of catalog-size quantities only. Federal regulations may apply to empty container. State and/or local regulations may be different. Dispose of in accordance with all local, state and federal regulations or contract with a licensed chemical disposal agency.

Section 14 Transport information

UN/NA number: UN1170 Shipping name: Ethanol solution

Reportable Quantity: 5,000 lbs (2270 kg) Hazard class: 3 Packing group: || Marine pollutant: No

2020 ERG Guide # 127 **Exceptions:** Limited quantity equal to or less than 1 L

Section 15 Regulatory information

A chemical is considered to be listed if the CAS number for the anhydrous form is on the Inventory list.

Component	TSCA	CERLCA (RQ)	RCRA code	DSL	NDSL	CA Prop 65
Ethanol	Listed	Not listed	D001	Listed	Not listed	▲ WARNING -Cancer and Reproductive Harm - www.P65Warnings.ca.gov.
Methanol	Listed	5,000 lbs.	U154	Listed	Not listed	
Isopropanol	Listed	Not listed	Not listed	Listed	Not listed	

Section 16 Other information

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. NTP: National Toxicology Program, IARC: International Agency for Research on Cancer, OSHA: Occupational Safety and Health Administration, STOT: Specific Target Organ Toxicity, SE: Single Exposure, RE: Repeated Exposure, ERG: Emergency Response Guidebook

Revision Date: September 8, 2022 Supercedes: September 24, 2020 Form 06/2015

Section 1 Identification Page E1 of E2

INNOVATING SCIENCE

"Cutting edge science for the classroom"

221 Rochester Street Avon, NY 14414-9409 (585) 226-6177 CHEMTREC 24 Hour Emergency Phone Number (800) 424-9300 For laboratory and industrial use only. Not for drug, food or household use.

Product METHYLENE BLUE CHLORIDE, 1% ALCOHOLIC SOLUTION

Synonyms | Methylene Blue Solution, 1% Alcoholic / Methylene Blue Alcohol/Water Solution

Section 2 Hazards identification

Signal word: DANGER Pictograms: GHS02 / GHS07

SDS No.: MM0450

Target organs: Central nervous system, Liver, Kidneys.





GHS Classification:

Flammable liquid (Category 2) Eye irritation (Category 2) STOT-SE (Category 3)

GHS Label information: Hazard statement(s):

H225: Highly flammable liquid and vapour. H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

Precautionary statement(s):

P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233: Keep container tightly closed.

P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P261: Avoid breathing mist/vapours/spray.

P264: Wash hands thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for 15 minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P312: Call a POISON CENTER or doctor if you feel unwell.

P337+P313: If eye irritation persists: Get medical attention.

P370+P378: In case of fire: Use dry chemical, alcohol foam, carbon dioxide or water spray to extinguish.

P403+P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

P501: Dispose of contents/container to a licensed chemical disposal agency in

accordance with local/regional/national regulations.

Hazards not otherwise classified:

Health hazards not otherwise classified (HHNOC) - Not Known Physical hazards not otherwise classified (PHNOC) - Not Known

Section 3 Composition / informa	tion on ingredients			
Chemical Name	CAS#	%	EINECS	
Isopropyl alcohol	67-63-0	50.0%	200-661-7	
Water	7732-18-5	48.8%	231-791-2	
Methylene blue chloride (C.I. No. 52015)	61-73-4	1.0%	200-515-2	
Sodium benzoate	532-32-1	0.2%	208-534-8	

Section 4 First aid measures

INGESTION: MAY BE HARMFUL IF SWALLOWED. Call physician or Poison Control Center immediately. Induce vomiting only if advised by appropriate medical personnel. Never give anything by mouth to an unconscious person.

INHALATION: MAY BE HARMFUL IF INHALED. CAUSES RESPIRATORY TRACT IRRITATION. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

EYE CONTACT: CAUSES EYE IRRITATION. Check for and remove contact lenses. Flush thoroughly with water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get immediate medical attention.

SKIN ABSORPTION: MAY BE HARMFUL IF ABSORBED THROUGH SKIN. MAY CAUSE SKIN IRRITATION. Remove contaminated clothing. Flush thoroughly with mild soap and water. If irritation occurs, get medical attention.

Section 5 Fire fighting measures

Suitable Extinguishing Media: Carbon dioxide, dry chemical, dry sand, alcohol foam.

Protective Actions for Fire-fighters: In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus and full protective gear. Use water spray to keep fire-exposed containers cool.

Specific Hazards: During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Vapors formed from this product are heavier than air and may travel along the ground to a distant source of ignition and flash back instantly. Flame may not be visible in daylight.

Section 6 Accidental release measures

Personal Precautions: Evacuate personnel to safe area. Use proper personal protective equipment as indicated in Section 8. Provide adequate ventilation.

Environmental Precautions: Avoid runoff into storm sewers and ditches which lead to waterways

Containment and Cleanup: Remove all sources of ignition. Absorb with inert dry material, sweep or vacuum up and place in a suitable container for proper disposal. Wash spill area with soap and water.

Section 7 Handling and storage Page E2 of E2

Precautions for Safe Handling: Read label on container before using. Do not wear contact lenses when working with chemicals. Keep out of reach of children. Avoid contact with eyes, skin and clothing. Do not inhale vapors, spray or mist. Use with adequate ventilation. Avoid ingestion. Wash thoroughly after handling. Remove and wash clothing before reuse.

Conditions for Safe Storage: Store in a cool, dry, well-ventilated area away from incompatible substances. Keep away from ignition sources.

Section 8	Exposure controls / personal protection							
Exposure Limits:	Chemical Name	ACGIH (TLV)	OSHA (PEL)	NIOSH (REL)				
Exposure Limits:	Isopropanol	TWA: 200 ppm / STEL: 400 ppm	TWA: 400 ppm / 980 mg/m ³	TWA: 400 ppm / STEL: 500 ppm				

Engineering controls: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower and fire extinguishing material. Personnel should wear safety glasses, goggles, or faceshield, lab coat or apron, appropriate protective gloves. Use adequate ventilation to keep airborne concentrations low.

Respiratory protection: None should be needed in normal laboratory handling at room temperatures. If misty conditions prevail, work in fume hood or wear a NIOSH/MSHA-approved respirator.

Section 9 Physical and chemical properties

Appearance: Clear, colorless liquid.

Odor: Aromatic odor.

Odor threshold: Data not available.

pH: Data not available.

Melting / Freezing point: Approximately -21.6°C (-7°F)

Boiling point: 80°C (176°F) Flash point: 23.9°C (75.5°F) TCC Evaporation rate (Butyl acetate = 1): >1
Flammability (solid/gas): Data not available.

Explosion limits: Lower / Upper: 2% / 12% [Pure IPA] Vapor pressure (mm Hg): 33 mm @20°C [Pure IPA]

Vapor density (Air = 1): 2.1 [Pure IPA] Relative density (Specific gravity): 0.8 Solubility(ies): Complete in water. Partition coefficient: (n-octanol / water): Data not available Auto-ignition temperature: 399°C (750°F) ASTM-E659-78 [Pure IPA] Decomposition temperature: Data not available.

Viscosity: Data not available.

Molecular formu la: Mixture

Molecular weight: Mixture

Section 10 Stability and reactivity

Chemical stability: Stable Hazardous polymerization: Will not occur. Conditions to avoid: Excessive temperatures, heat, sparks, open flame and other sources of ignition.

Incompatible materials: Strong oxidizing materials, caustics, aluminums, metals, nitroform, oleum, chlorinated compounds can react vigorously with this alcohol.

Hazardous decomposition products: Oxides of carbon.

Section 11 Toxicological information

Acute toxicity: Oral-rat LD50: 4396 mg/kg ; Inhalation-rat LC50: 72.6 mg/L/4 hours ; Dermal-rat LD50: 12,000 mg/kg [Isopropanol]

Skin corrosion/irritation: Skin-rabbit - Slight irritant. Serious eye damage/irritation: Eyes-rabbit - Irritating. Respiratory or skin sensitization: Not sensitizing Germ cell mutagenicity: Data not available

Carcinogenity: Data not available

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

IARC classified: Group 3: Not classifiable as to its carcinogenicity to humans

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Ca Prop 65: This product does not contain any chemicals known to the State of California to cause cancer or reproductive toxicity.

Reproductive toxicity: Data not available

STOT-single exposure: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT-repeated exposure: Data not available **Aspiration hazard:** Data not available

Potential health effects:

Inhalation: Inhalation of high vapor concentrations may cause central nervous system depression resulting in dizziness, drowsiness, nausea, vomiting, inability to concentrate and irritation of the throat. Continued inhalation may result in unconsciousness and death.

Ingestion: Aspiration hazard. Liquid can directly enter the lungs (aspirated) when swallowed or vomited. Serious lung damage and possible fatal chemical pneumonia can develop if this occurs.

Skin: Prolonged or repeated contact may cause irritation and drying, cracking and defatting of the skin which can lead to dermatitis.

Eyes: Contact causes burning sensation, redness, swelling, and/or blurred vision. **Signs and symptoms of exposure:** See Potential health effects above.

Additional information: RTECS #: NT8050000 [Isopropanol]

Section 12 Ecological information

Toxicity to fish: Pimephales promelas (Fish, fresh water) LC50: 9640 mg/L/96 hours [Isopropanol]

Toxicity to daphnia and other aquatic invertebrates: Artemia salina (Crustacea), EC50 = >10,000 mg/L/24 hours [Isopropanol]

Toxicity to algae: Scenedesmus quadricauda (Algae), LOEC50 = 1,800 mg/L/7 days [Isopropanol]

Persistence and degradability: No data available

Mobility in soil: No data available

PBT and vPvB assessment: No data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Section 13 Disposal considerations

These disposal guidelines are intended for the disposal of catalog-size quantities only. Federal regulations may apply to empty container. State and/or local regulations may be different. Dispose of in accordance with all local, state and federal regulations or contract with a licensed chemical disposal agency.

Section 14 Transport information

UN/NA number: UN1987 Shipping name: Alcohols, n.o.s., (Isopropanol)

Hazard class: 3 Packing group: ||| Reportable Quantity: No Marine pollutant: No

Exceptions: Limited quantity equal to or less than 5 L 2020 ERG Guide # 127

Section 15 Regulatory information

A chemical is considered to be listed if the CAS number for the anhydrous form is on the Inventory list.

Component	TSCA	CERLCA (RQ)	RCRA code	DSL	NDSL	CA Prop 65
Isopropyl alcohol	Listed	Not listed	Not listed	Listed		This product does not contain any chemicals known to the State of California to cause cancer or reproductive toxicity.

Section 16 Other information

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. NTP: National Toxicology Program, IARC: International Agency for Research on Cancer, OSHA: Occupational Safety and Health Administration, STOT: Specific Target Organ Toxicity, SE: Single Exposure, RE: Repeated Exposure, ERG: Emergency Response Guidebook.

Form 06/2015 Revision Date: October 24, 2022 Supercedes: October 8, 2020

Identification Section 1 Page E1 of E2

INNOVATING SCIENCE

"Cutting edge science for the classroom"

221 Rochester Street Avon, NY 14414-9409 (585) 226-6177

CHEMTREC 24 Hour Emergency Phone Number (800) 424-9300

For laboratory and industrial use only. Not for drug, food or household use.

METHYLENE BLUE SOLUTION (LOEFFLER'S) Product

Synonyms Loeffler's Methylene Blue Stain

Section 2 Hazards identification

Signal word: DANGER

Pictograms: GHS02 / GHS08 / GHS06

Target organs: Eyes, Central nervous system, Liver, Kidneys.







GHS Classification:

Flammable liquid (Category 2) Acute toxicity, inhalation (Category 3) Skin irritation (Category 2) Eve irritation (Category 2B) STOT-SE (Category 2) STOT-SE (Category 3)

GHS Label information: Hazard statement:

H225: Highly flammable liquid and vapour.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H336: May cause drowsiness or dizziness. H371: May cause damage to organs.

Precautionary statement:

P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P260: Do not breathe mist/vapours/spray.

P264: Wash hands thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for 15 minutes. Remove

contact lenses, if present and easy to do. Continue rinsing

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing

P312: Call a POISON CENTER or doctor if you feel unwell.

P332+P313: If skin irritation occurs: Get medical attention.

P337+P313: If eye irritation persists: Get medical attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P403+P233: Store in a well-ventilated place. Keep container tightly closed. P501: Dispose of contents/container to a licensed chemical disposal agency in

accordance with local/regional/national regulations.

Hazards not otherwise classified:

Health hazards not otherwise classified (HHNOC) - Not Known Physical hazards not otherwise classified (PHNOC) - Not Known

Section 3 Composition / information on ingredients					
Chemical Name	CAS#	%	EINECS		
Ethyl alcohol, 95% denatured*	64-17-5	99.45%	200-578-6		
Methylene blue chloride	61-73-4	0.5%	200-515-2		
Potassium hydroxide	1310-58-3	0.04%	215-181-3		
Water	7732-18-5	Balance	231-791-2		
*Denaturants:					
Isopropyl alcohol	67-63-0		200-661-7		
Methanol	67-56-1		200-659-6		
Methyl isobutyl ketone	108-10-1		203-550-1		

Section 4 First aid measures

INGESTION: MAY BE HARMFUL IF SWALLOWED. Call physician or Poison Control Center immediately. Induce vomiting only if advised by appropriate medical personnel. Never give anything by mouth to an unconscious person.

INHALATION: MAY BE HARMFUL IF INHALED. CAUSES RESPIRATORY TRACT IRRITATION. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

EYE CONTACT: CAUSES EYE IRRITATION. Check for and remove contact lenses. Flush thoroughly with water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get immediate medical attention.

SKIN ABSORPTION: MAY BE HARMFUL IF ABSORBED THROUGH SKIN. CAUSES SKIN IRRITATION. Remove contaminated clothing. Flush thoroughly with mild soap and water. If irritation occurs, get medical attention.

Section 5 Fire fighting measures

Suitable Extinguishing Media: Carbon dioxide, dry chemical, dry sand, alcohol foam.

Protective Actions for Fire-fighters: In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus and full protective gear. Use water spray to keep

Specific Hazards: During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Vapors formed from this product are heavier than air and may travel along the ground to a distant source of ignition and flash back instantly. Flame may not be visible in daylight.

Accidental release measures

Personal Precautions: Evacuate personnel to safe area. Use proper personal protective equipment as indicated in Section 8. Provide adequate ventilation.

Environmental Precautions: Avoid runoff into storm sewers and ditches which lead to waterways

Containment and Cleanup: Remove all sources of ignition. Absorb with inert dry material, sweep or vacuum up and place in a suitable container for proper disposal. Wash spill area with soap and water.

Precautions for Safe Handling: Read label on container before using. Do not wear contact lenses when working with chemicals. Keep out of reach of children. Avoid contact with eyes, skin and clothing. Do not inhale vapors, spray or mist. Use with adequate ventilation. Avoid ingestion. Wash thoroughly after handling. Remove and wash clothing before reuse.

Conditions for Safe Storage: Store in a cool, dry, well-ventilated area away from incompatible substances. Keep away from ignition sources. Protect from light.

Section 8	Exposure controls / personal protection					
Exposure Limits:	Chemical Name	ACGIH (TLV)	OSHA (PEL)	NIOSH (REL)		
	Ethanol	STEL: 1000 ppm / 1880 mg/m ³ (A3)	TWA: 1000 ppm / 1900 mg/m ³	TWA: 1000 ppm / 1900 mg/m ³		

Engineering controls: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower and fire extinguishing material. Personnel should wear safety glasses, goggles, or faceshield, lab coat or apron, appropriate protective gloves. Use adequate ventilation to keep airborne concentrations low.

Respiratory protection: None should be needed in normal laboratory handling at room temperatures. If misty conditions prevail, work in fume hood or wear a NIOSH/MSHAapproved respirator.

Section 9 Physical and chemical properties

Appearance: Clear, blue liquid. Odor: Mild characteristic odor. Odor threshold: Data not available.

pH: Data not available Melting / Freezing point: -114°C (-173°F)* Boiling point: 74-80°C (165.2-176°F)*

Flash point: 5°C (41°F)*

Evaporation rate (Butyl acetate = 1): Ca 2* Flammability (solid/gas): Data not available. Explosion limits: Lower / Upper: 4.0%(V) / 20.0%(V)* Vapor pressure (mm Hg): Ca 50 @ 20°C'

Vapor density (Air = 1): Ca 1.5*

Relative density (Specific gravity): 0.7919-0.7955°C @ 60/60°F*

Solubility(ies): Soluble in water.

Partition coefficient: (n-octanol / water): Low Pow: -.32*

Auto-ignition temperature: 400°C (752°F)* Decomposition temperature: Data not available Viscosity: Data not available.

Molecular formula: Mixture Molecular weight: Mixture

*[Ethanol]

Section 10 Stability and reactivity

Chemical stability: Stable Hazardous polymerization: Will not occur. Conditions to avoid: Excessive temperatures, heat, sparks, open flame and other sources of ignition.

Incompatible materials: Strong oxidizers, inorganic acids and halogens.

Hazardous decomposition products: Oxides of carbon.

Section 11 **Toxicological information**

Acute toxicity: Oral-rat LD50: 7060 mg/kg; Inhalation-rat LC50: 124.7 mg/l/4hours [Ethanol]

Skin corrosion/irritation: Skin-rabbit - Slight irritant. Serious eye damage/irritation: Eyes-rabbit - Severe irritant. Respiratory or skin sensitization: Data not available

Germ cell mutagenicity: Data not available

Carcinogenity: Data not available

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

IARC classified: Group 3: Not classifiable as to its carcinogenicity to humans. [Isopropanol]

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

CA Prop 65: A WARNING! : This product can expose you to chemicals including Methanol and Methyl isobutyl ketone, which are known to the State of California to cause cancer and birth defects or other reproductive harm.

Reproductive toxicity: Data not available

STOT-single exposure: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT-repeated exposure: Data not available Aspiration hazard: Data not available

Potential health effects:

Inhalation: Inhalation may cause dizziness, drowsiness, nausea, vomiting, inability to concentrate and irritation of the throat. Ingestion: Ingestion causes dizziness, drowsiness, decreased reaction, euphoria, nausea, vomiting, staggering gait and coma.

Skin: Contact with skin causes irritation defatting on prolonged contact.

Eves: Contact with eves may cause blindness.

Signs and symptoms of exposure: See Potential health effects above.

Additional information: RTECS #: KQ6300000 [Ethanol]

Section 12 **Ecological information**

Toxicity to fish: Oncorhynchus mykiss (fish, fresh water), LC50 = 11,200 mg/l/24 hours [Ethanol]

Toxicity to daphnia and other aquatic invertebrates: Daphnia magna (Crustacia), EC50 = 10,800 mg/l/24 hours [Ethanol, 99.8% pure]

Toxicity to algae: Chlorella pyrenoidosa (Algae), EC50 = 9,310 mg/l/growth rate [Ethanol, absolute] Persistence and degradability: No data available Bioaccumulative potential: No data available Mobility in soil: No data available PBT and vPvB assessment: No data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Disposal considerations

These disposal guidelines are intended for the disposal of catalog-size quantities only. Federal regulations may apply to empty container. State and/or local regulations may be different. Dispose of in accordance with all local, state and federal regulations or contract with a licensed chemical disposal agency.

Section 14 Transport information

UN/NA number: UN1170 Shipping name: Ethanol solution

Reportable Quantity: 5,000 lbs (2270 kg) Hazard class: 3 Packing group: || Marine pollutant: No

2020 ERG Guide # 127 **Exceptions:** Limited quantity equal to or less than 1 L

Section 15 Regulatory information

A crieffical is considered to be listed if the CAS flumber for the analydrous form is on the inventory list.						
Component	TSCA	CERLCA (RQ)	RCRA code	DSL	NDSL	CA Prop 65
Ethanol Methanol	Listed Listed	Not listed 5,000 lbs.	D001 U154	Listed Listed	Not listed Not listed	⚠ WARNING -Cancer and Reproductive Harm - www.P65Warnings.ca.gov.
Isopropanol	Listed	Not listed	Not listed	Listed	Not listed	- www.P65vvarnings.ca.gov.

Section 16 Other information

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. NTP: National Toxicology Program, IARC: International Agency for Research on Cancer, OSHA: Occupational Safety and Health Administration, STOT: Specific Target Organ Toxicity, SE: Single Exposure, RE: Repeated Exposure, ERG: Emergency Response Guidebook

Revision Date: October 24, 2022 Supercedes: October 8, 2020 Form 06/2015